

## Lunar ROADSTER

(Robotic Operator for Autonomous Development of Surface Trails and Exploration Routes)

"Starting with a foothold on the Moon, we pave the way to the cosmos"



### **The Team**











Bhaswanth Ayapilla

Simson D'Souza

Boxiang (William) Fu



Dr. William "Red" Whittaker

#### **Agenda**


- 1. Validation: Tuning, testing and integration
- 2. Perception: Geometric feature extraction, online implementation
- 3. Navigation: Test and tune the global planners and controllers on the rover
- 4. Planning: Parsing robot poses and integrating perception, validation, and navigation
- 5. Localization: Implement SkyCam methodology




#### **Goal:** Validation Stack

#### **Implementation:**

- Obtains most recent point cloud feed from the ZED camera
- Voxel downsampling, and builds a KdTree
- Surface normal estimation and calculate per-point slope from the vertical z-axis
- Nearest neighbor smoothing and masking to filter out phantom points and walls/edges
- Compute aggregate slope statistics over several frames



Validation Success = False Max Slope = 17.93 deg




Validation Success = True Max Slope = 1.73 deg

### **Goal: Perception Stack**


- Online implementation on Orin - DONE
- Crater Center Coordinates in Camera Frame (X,Y,Z)- DONE
  - Transform to staticworld frame INPROGRESS
- Crater Diameter (in meters)-DONE




### **Goal:** Navigation stack




- Global Planner tested and tuned
- Visualization shows gradable and ungradable craters
- Converted into ROS Service
- Blue line shows latitude
- Green line shows planned path
- Deviation statistics are calculated



## **Goal:** Navigation stack





Global Controller tested and tuned

#### **Goal:** Planning Stack - now merged with Perception

#### **Robot pose parsing complete (ROS Service)**

- a. Obtains crater geometry from perception (integrated)
- b. Creates source, sink and offset poses for manipulation
- c. All hyperparameters are in yaml files
- d. Code developed with BEN in mind and will be easily integrated
- e. Validation will be integrated into BEN directly.
- f. Next step testing and tuning parameters

### **Goal: Sky Cam Localization**

#### **Implementation:**

- Detects ceiling light pattern using fisheye camera
- Filters "of interest" pixels by brightness
- Levenberg–Marquardt optimization to fit ceiling grid
- Convert camera 2D coordinates to 3D coordinates using ceiling height

#### **Issues:**

 Roll and pitch causes pose to drift, trying mechanical gimbal and software fixes



## **Risk Management**

Risk ID	Risk Title	Risk Owner	Risk Type:			Logis	stics			
R30	No spares available	Team								
Description	1	Date Added		5						
		3/4/2025	poo	4					$\bigotimes$	
Discontinue	ed model, spare parts unavailable	Date Updated	Likelihood	3						
		8/30/2025	Ë	2						
Consequence										
The whole project falling through, or redo almost all subsystems on a different rover.					1	2 Coi	3 iseque	4 nce	5	
Action/Milestone Success Criteria				Date Planned				Date Implemented		
Check out e	Bay and other similar platforms for spares	Successfully find exact spares on these platforms	3/6/2025			9/22/2025				
Check out a	nd stock similar parts if not same	Successfully find and stock similar parts	3/6/2025			9/22/2025				
Find a twin	rover that was used by a previous team on campus	Successfully find the twin rover and scavenge parts		3/6/	′2025		3/7/2025			
F. 11	parts - a slightly smaller pinion and motor set	Spares problem will be		0/10	/2025		9/22/2025			

### **Risk Management**

**Risk Owner** 

Risk Type:

Logistics

Risk ID

**Risk Title** 

R36	PRL Moonyard Access	William	_							
Descriptio	n	Date Added		5						
Coouring a N	John word assess for testing /domes will be	8/29/2025	poor	4						
	Ioonyard access for testing/demos will be and challenging	Date Updated	Likelihood	3						
1000110000		8/29/2025	17	2				$\otimes$		
Conseque	nce			1				$\oplus$		
No testbed	available for testing and/or FVD			1	1	2 Co	3 nseque	4 ence	5	
									Date	
Action/Mi	lestone	Success Criteria	Date Planned				Implemented			
	discuss a testing and demo plan with Prof. Red avid Wettergreen beforehand and reserve slots	Successfully meet and discuss the schedule of high priority projects	9/11/2025				9/11/2025			
Complete I controlled	Medical Evaluation to get unrestricted but access	get unrestricted but  Successfully complete the Medical Evaluation and get unrestricted access to the Moonyard  9/5/2025				9/11/2025				
Respirator	Training	Complete training and get custom masks		9/30	/2025	5				

### **Risk Management**

Risk ID	Risk Title	Risk Owner	Risk	Risk Type:			Technical				
R34	Arduino requires reset before operation	Bhaswanth	_								
Description	on	Date Added		5							
	eeds to be manually reset each time before starting or switching between autonomy and teleoperation	3/4/2025  Date Updated  4/10/2025	Likelihood	3							
Conseque		2		D							
Slows down setup time and impacts operational readiness, delaying mission start and mode transitions.						2 Cor	3 aseque	4 ence	5		
Action/Milestone Success Criteria						Date Planned			Date Implemented		
Check USB port permissions and drivers issues on Jetson consistent serial connection without reset					4/26/2025				9/5/2025		
Verify that Arduino is connected via USB 3.0 instead of USB Ensure stable high-speed communication					26/2025 9/5/			9/5/20	)25		
				4/26/2025							
Check for loss to Ard	ROS node frequency mismatches causing packet luino	Match ROS publish/subscribe rates		4/26	/2025	5	ç	9/5/20	)25		


## **Issues Log**

114	09/14/2025		Team	Steer pinion tooth chipped and worn-out due to wear-and-tear. Unable to find exact replacement for the pinion	Replace with similar pinion that has different tooth count     Switch to using another chassis		
115	09/14/2025	10/07/2025	Ankit Aggarwal Deepam Ameria Simson D'Souza	Wires keep on coming loose during operations due to bad soldering	Re-solder every wire     Switch to plug     connectors and buy     adaptors for the     RoboClaws and motors	Switched wiring to use plug connectors	This allows us to stop worrying about loose wiring due to bad soldering
I16	10/04/2025		Team	Unable to obtain rear steer motor encoder feedback	Recheck wiring     permutations to see     which one is correct     Retrace wiring to make     sure everything is wired     correctly		
117	10/04/2025		Теат	Front steer has power issue	Recheck front steer power connections with the RoboClaw connectors     Check how the rear steer power connections are connected and try to copy		

#### **Future Work**

#### PR 11 Goals:

- Localization QA & compensation for roll and pitch
- Validation QA & integration with BEN stack
- Navigation QA
- Planning QA
- Perception QA
- Hardware QA





# THANKS!

Team Lunar ROADSTER

